

AMENDMENTS TO THE CLAIMS

This listing of claims replaces all prior versions, and listings, of claims in the application:

1. (Currently Amended) An airbag apparatus for a front passenger seat of a vehicle comprising:

a container that has a pair of opposing sides; and

an airbag that is folded and accommodated within the container;

wherein one of the pair of the opposing sides includes a locking part for connecting to a vehicle instrument panel and the other of the pair of opposing sides includes a fixing part for connecting to the instrument panel,

wherein the fixing part includes two members that extend substantially in parallel with each other,

wherein the fixing part is configured to receive a wall section that extends from a rear surface of the instrument panel between the two members,

wherein the wall section includes at least one opening for insertion of one of the two substantially parallel members, and

wherein the wall section includes a leg piece that extends in a direction substantially parallel to the instrument panel and away from the container.

2. (Original) The apparatus of Claim 1, wherein the two members extend in a direction substantially perpendicular to the pair of opposing sides and away from the container.

3. (Original) The apparatus of Claim 1, wherein the locking part is hook shaped.

4. (Previously Presented) The apparatus of Claim 1, wherein the two members are connected together to form a clamp for the wall section.

5. (Canceled)

6. (Currently Amended) A setting structure for an airbag apparatus for a front passenger seat of a vehicle having an instrument panel,

wherein the airbag apparatus comprises:

a container that has a pair of opposing sides; and

an airbag that is folded and accommodated within the container,

wherein the setting structure includes an arrangement wherein each of the opposing sides is connected to a backside of the instrument panel,

wherein one of the opposing sides includes a clamp that has two parallel members that connect to a wall section of the instrument panel, which wall section extends toward the container,

wherein the wall section includes at least one opening for insertion of one of the two parallel members, and

wherein the wall section includes a leg piece that extends in a direction substantially parallel to the instrument panel and away from the container.

7. (Canceled)

8. (Original) The structure of Claim 6, wherein the leg piece is positioned between the two parallel members.

9. (Previously Presented) The structure of Claim 8, wherein the leg piece is connected to the members by at least one bolt.

10. (Previously Presented) The structure of Claim 6, wherein the other of the opposing sides includes a hook-shaped extension that connects with a downwardly extending portion of the instrument panel.

11. (Currently Amended) An airbag apparatus for a front passenger seat of a vehicle comprising:

a container that has a pair of opposing sides; and

an airbag that is folded and accommodated within the container;

wherein one of the pair of the opposing sides includes a locking part for connecting to a vehicle instrument panel and the other of the pair of opposing sides includes a fixing part for connecting to the instrument panel,

wherein the fixing part includes two substantially parallel, non-coplanar members that extend in a direction substantially parallel to the instrument panel and away from the ~~container, and container,~~

wherein the fixing part is configured to receive a wall section that extends from a rear surface of the instrument panel between the two members, and

wherein the wall section includes at least one opening for insertion of one of the two substantially parallel members.

12. (Previously Presented) The apparatus of Claim 11, wherein the two members extend in a direction substantially perpendicular to the pair of opposing sides and away from the container.

13. (Previously Presented) The apparatus of Claim 11, wherein the locking part is hook shaped.

14. (Previously Presented) The apparatus of Claim 11, wherein the two members are connected together to form a clamp for the wall section.

15. (New) An airbag apparatus for a front passenger seat of a vehicle comprising:  
a container that has a pair of opposing sides; and  
an airbag that is folded and accommodated within the container;  
wherein one of the pair of the opposing sides includes a locking part for connecting to  
a vehicle instrument panel and the other of the pair of opposing sides includes a fixing part  
for connecting to the instrument panel,  
wherein the locking part includes a hooked shaped portion that passes through a first  
wall section that extends from a rear surface of the instrument panel,  
wherein the fixing part includes two members that extend substantially in parallel  
with each other,  
wherein the fixing part is configured to receive a second wall section that extends  
from the rear surface of the instrument panel between the two members,  
wherein the second wall section includes a leg piece that extends in a direction  
substantially parallel to the instrument panel and away from the container.

16. (New): The apparatus of claim 15, wherein the hook shaped portion of the  
locking part comprises two sidewalls and a bottom wall, and wherein one of the sidewalls is  
part of the opposing side that includes the locking part.

17. (New) An airbag apparatus for a front passenger seat of a vehicle comprising:  
a container that has a pair of opposing sides; and  
an airbag that is folded and accommodated within the container;  
wherein one of the pair of the opposing sides includes a hook shaped locking part  
configured to pass through and connect to a vehicle instrument panel and the other of the pair  
of opposing sides includes a fixing part for connecting to the instrument panel,  
wherein the fixing part includes two substantially parallel, non-coplanar members that  
extend in a direction substantially parallel to the instrument panel and away from the  
container, and  
wherein the fixing part is configured to receive a wall section that extends from a rear  
surface of the instrument panel between the two members

18. (New): The apparatus of claim 17, wherein the hook shaped portion of the  
locking part comprises two sidewalls and a bottom wall, and wherein one of the sidewalls is  
part of the opposing side that includes the locking part.